

XP20 |  **R290**

Model	X20-24P	X20-34P
Advised pool volume (m ³)	25~45	40~60
Operating air temperature (°C)	-15~43	
Performance Condition: Air 26°C, Water 26°C, Humidity 80%		
Heating capacity (kW) in Turbo mode	24.0	33.8
Heating capacity (kW) in Smart mode	19.6	28.4
COP	17.0-6.8	17.1-6.7
COP at 50% capacity	11.5	11.6
Performance Condition: Air 15°C, Water 26°C, Humidity 70%		
Heating capacity (kW) in Turbo mode	15.7	22.9
Heating capacity (kW) in Smart mode	12.9	19.2
COP	7.9-4.8	7.9-5.1
COP at 50% capacity	6.9	7.0
Sound pressure at 1m dB(A)	42.1-53.6	43.1-54.9
Sound pressure of 50% capacity at 1m dB(A)	46.3	47.1
Sound pressure at 10m dB(A)	22.1-33.6	23.1-34.9
Compressor	Twin-rotary DC-inverter	
Heat exchanger	Spiral titanium tube in PVC	
Casing	Aluminum-alloy Casing	
Power supply	230V~/1Ph/50Hz	
Rated input power at air 15°C (kW)	0.33-3.27	0.49-4.49
Rated input current at air 15°C (A)	1.43-14.22	2.13-19.52
Advised water flux (m ³ /h)	6.5-8.5	10-12
Water pipe in-out size (mm)	50	
Net Dimension L × W × H (mm)	995×432×750	1074×539×947
Net weight (kg)	95	118

* The advised pool volume indicated applies under following conditions: Swimming pool is well covered; system runs at least 15 hours per day;
 * The final specs will be accordance with the specs on the product.



Nile Water Corporation
 Abu Tig Marina MB 17-2 'Nile Water Square'
 84513 El Gouna - Red Sea, Egypt





UP TO COP 20

20 times energy saving, another groundbreaking COP performance



130% TURBOSILENCE

Heating efficiency perfectly increased with maximum running speed



GWP 0.02 ONLY

R290 Driven, Real Low Carbon